SAFETY DATA SHEET



1. Identification

Product identifier UNITED COATINGS ELASTUFF 120 ROLLER GRADE COATING PART B

Other means of identification

Product Code

Recommended use Polyurethane elastomer coating.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GAF

1 Campus Drive

Parsippany, NJ 07054 USA

Telephone 1-800–766–3411

Emergency phone number CHEMTREC [DAY OR NIGHT] 1-800-424-9300

Within USA and CANADA 1-800-424-9300 Outside USA and Canada: 1 703-741-5970

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, dermal Category 4
Serious eye damage/eye irritation Category 1
Carcinogenicity Category 2
Hazardous to the aquatic environment, acute Category 3

Environmental hazards Hazardous to the aquatic environment, a

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed. Harmful in contact with skin. Causes serious eye damage. Suspected of

causing cancer. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If

in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Rinse mouth. Take off

contaminated clothing and wash before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: UNITED COATINGS ELASTUFF 120 ROLLER GRADE PART B
Version #: 02 Revision date: 11-23-2015

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Ethyl-1,3-hexanediol		94-96-2	5 to <10
Titanium Dioxide		13463-67-7	1 to <5
Zeolites		1318-02-1	1 to <5
Diethyltoluenediamine		68479-98-1	0.1 to <1
Non-Hazardous Ingredients			80 to <90

4. First-aid measures

Inhalation Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical advice/attention if you feel unwell. Get medical Skin contact

attention if irritation develops and persists. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Get medical advice/attention if you feel unwell.

Most important

symptoms/effects, acute and delayed

Severe eve irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Powder. Carbon dioxide (CO2).

sheet to the doctor in attendance.

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

During fire, gases hazardous to health may be formed.

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: UNITED COATINGS ELASTUFF 120 ROLLER GRADE PART B

SDS US Version #: 02 Revision date: 11-23-2015 2/8 SDS 3056

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit Value			-
Components	Туре	Value	Form
Titanium Dioxide (CAS	TWA	10 mg/m3	
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Biological limit values

controls

Appropriate engineering

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash

work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Not available.
Odor Not available.

Material name: UNITED COATINGS ELASTUFF 120 ROLLER GRADE PART B

Version #: 02 Revision date: 11-23-2015

Not available. Odor threshold Not available. Ha

Melting point/freezing point -40 °F (-40 °C) estimated

Initial boiling point and boiling

range

471.56 °F (244.2 °C) estimated

260.0 °F (126.7 °C) estimated Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

Vapor pressure 0.002 hPa estimated

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 680 °F (360 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

8.31 lbs/gal Density

Combustible IIIB estimated Flammability class

Percent volatile 0.33 % Specific gravity 1

VOC 0.023473 lbs/gal Material estimated

> 0.023473 lbs/gal Regulatory estimated 2.81277 g/l Material estimated

2.81277 g/l Regulatory estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. Conditions to avoid

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Harmful in contact with skin. Eye contact Causes serious eye damage.

Harmful if swallowed. Ingestion

Material name: UNITED COATINGS ELASTUFF 120 ROLLER GRADE PART B

Version #: 02 Revision date: 11-23-2015 SDS 3056

4/8

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Harmful in contact with skin. Harmful if swallowed. **Acute toxicity**

Components **Species Test Results**

2-Ethyl-1,3-hexanediol (CAS 94-96-2)

Acute Oral

LD50 Mouse 1900 mg/kg

Rat 1400 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Suspected of causing cancer. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Zeolites (CAS 1318-02-1) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects**

12. Ecological information

Harmful to aquatic life with long lasting effects. **Ecotoxicity**

Components		Species	Test Results
2-Ethyl-1,3-hexanedic	ol (CAS 94-96-2)		
Aquatic			
Fish	LC50	Channel catfish (Ictalurus punctatus)	624 mg/l, 96 hours
Titanium Dioxide (CAS	S 13463-67-7)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Material name: UNITED COATINGS ELASTUFF 120 ROLLER GRADE PART B

Version #: 02 Revision date: 11-23-2015

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Not established.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Diethyltoluenediamine (CAS 68479-98-1)

1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

> Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Material name: UNITED COATINGS ELASTUFF 120 ROLLER GRADE PART B Version #: 02 Revision date: 11-23-2015

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Titanium Dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4) Listed: February 21, 2003 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

N-Methyl-2-Pyrrolidone (CAS 872-50-4) Listed: June 15, 2001

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 03-12-2015 **Revision date** 11-23-2015

Version #

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 0 Instability: 0

Material name: UNITED COATINGS ELASTUFF 120 ROLLER GRADE PART B

Version #: 02 Revision date: 11-23-2015

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information

Product and Company Identification: Converted to GAF SDS

Material name: UNITED COATINGS ELASTUFF 120 ROLLER GRADE PART B

Version #: 02 Revision date: 11-23-2015