

## 1. Product Identification

---

|   |  |
|---|--|
| Product name  | S-1 Epoxy Sealer, Part B   |
| SDS Number  | F1400B00   |
| Product type  | Polyamide/solvent mixture  |
| Recommended use of the chemical and restrictions on use | Directed at, but not limited to, the sealing and coating of wood and fiber composites                          |
| Restrictions  | None known.  |
| Manufacturer/Supplier information                       |  |
| Company name  | SYSTEM THREE RESINS, INC.  |
| Address   | 8517 Commerce Place Dr NE<br>Lacey, WA 98516<br>United States  |
| Telephone   | 1-253-333-8118   |
| Website   | www.systemthree.com  |
| Email   | support@systemthree.com  |
| Emergency Contact                                       | CHEMTEL (U.S. and CANADA) 1-800-704-9215<br>CHEMTEL (Outside the U.S.) – Call Collect accepted +1-360-256-7365 |

## 2. Hazard(s) Identification

---

|  |  |
|--|--|
| Classification of substance or mixture/Signal Word | DANGER<br>Flammable liquid - Category 2<br>Skin Corrosion/Irritation – Category 2<br>Serious Eye Damage/Eye Irritation - Category 2<br>Skin Sensitization – Category 1<br>Toxic to Reproduction – Category 1<br>Specific Target Organ Toxicity (Single Exposure) [eyes, central nervous system (CNS), liver, kidneys] – Category 1<br>Specific Target Organ Toxicity (Repeated Exposure) [skin, eyes, central nervous system (CNS), respiratory tract, kidney, liver, blood system] – Category 1 |
|--|--|

GHS Label Elements  
Hazard Pictograms



|  |   |
|--|---|
| Hazard Statements/Classification of substance or mixture | H225 Highly flammable liquid and vapor<br>H315 Causes skin irritation.<br>H319 Causes serious eye irritation.<br>H317 May cause an allergic skin reaction.<br>H360 May damage fertility or the unborn child.<br>H370 Causes damage to organs.<br>H372 Causes damage to organs through prolonged or repeated exposure. |
| Precautionary statements                                 |   |

## Precautionary Statements

### Prevention

- P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/light/.../equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe fume/vapors/spray.  
P261 Avoid breathing fume/vapors/spray.  
P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves. Wear eye or face protection.

### Response

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/doctor.  
P314 Get medical advice/attention if you feel unwell.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P370 + P378 In case of fire: Use suitable extinguishing media to extinguish.

### Storage

- P362 + P364 Take off contaminated clothing and wash it before reuse.  
P403 + P235 Store in a well-ventilated place. Keep cool.

### Disposal

- P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified (HNOC)

None Available.

## 3. Composition/Information On Ingredients

| Chemical Name  | CAS Number | Content (%) |
|----------------|------------|-------------|
| Xylenes        | 1330-20-7  | 40 – 50%    |
| Polyaminoamide | 68410-23-1 | 20 – 25%    |
| n-Butanol      | 71-36-3    | 10 – 15%    |
| Acetone        | 108-10-1   | 10 – 15%    |
| Ethylbenzene   | 100-41-4   | 1 – 5%      |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

## 4. First-Aid Measures

### Skin contact

Remove contaminated clothing and shoes and wipe excess off skin. Flush skin with water for at least 15 minutes. Follow by washing in soap and water. If irritation occurs, seek medical attention. Do not reuse clothing until cleaned. Contaminated leather articles (shoes) cannot be decontaminated and should be destroyed.

### Eye contact

Flush with water for 15 minutes holding eye lids open. Seek medical attention.

**Ingestion** Do not give anything if victim is unconscious or very drowsy. DO NOT INDUCE VOMITING. Seek medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

**Inhalation** Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** No specific treatment.

---

## 5. Fire-Fighting Measures

**Suitable extinguishing media** Foam, carbon dioxide, dry chemical, water fog.

**Unsuitable extinguishing media** None known

**Specific hazards arising from the chemical** Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

**Hazardous decomposition products** Carbon oxides, aldehydes (including formaldehyde), and other organic compounds.

**Special protective actions for fire-fighters** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Further information** None known.

---

## 6. Accidental Release Measures

**Personal precautions** Wear proper personal protective equipment (PPE). Avoid direct contact with material.

**Emergency procedures** If material is spilled, avoid contact with material. Persons not wearing appropriate protective equipment should leave the area of the spill until cleanup is complete.

**Methods and materials for containment/cleanup** Ventilate area of leak or spill. Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank or drum. Remaining liquid may be taken up on clay, diatomaceous earth, sawdust or other absorbent, and shoveled into disposal container.

**Environmental precautions** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

---

## 7. Handling and Storage

**Precautions for safe handling** Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.

**Precautions/Recommendations for safe/proper storage**

Keep away from heat, sparks, and open flame, and out of the reach of pets or children. Securely fasten container lids and tops, and prevent products from sitting and below freezing temperatures. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

## 8. Exposure Controls/Personal Protection

### Occupational Exposure Limits

| Components     | CAS No.    | Type                             | Value   |
|----------------|------------|----------------------------------|---|
| Polyaminoamide | 68410-23-1 | Not established                  | Not established   |
| Xylene         | 1330-20-7  | ACGIH TLV (1996-05-18)           | TWA – 434 mg/m3 100 ppm   |
|                |            | Short Term Exposure Limit (STEL) | 651 mg/m3 150 ppm   |
|                |            | OSHA PEL (1993-06-30)            | TWA – 435 mg/m3 100 ppm   |
| Ethylbenzene   | 100-41-4   | ACGIH TLV (2011-09-30)           | TWA – 87 mg/m3 20 ppm   |
|                |            | Short Term Exposure Limit (STEL) | 543 mg/m3 125 ppm   |
|                |            | NIOSH REL (1994-06-01)           | TWA – 435 mg/m3 100 ppm   |
| Acetone        | 67-64-1    | ACGIH TLV                        | TWA – 250 ppm   |
|                |            | Short Term Exposure Limit (STEL) | 500 ppm   |
|                |            | NIOSH IDLH                       | IDLH – 2500 ppm<br>TWA – 250 ppm<br>TWA – 590 mg/m3                                 |
|                |            | OSHA PEL                         | TWA – 1800 mg/m3 750 ppm<br>STEL – 2400 mg/m3<br>TWA – 1000 ppm<br>TWA – 2400 mg/m3 |
| n-butanol      |            | ACGIH TLV                        | TWA – 20 ppm  |
|                |            | OSHA Z-1                         | PEL – 100 ppm 300 mg/m3   |

**Appropriate engineering controls**

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Individual protection measures/Personal protective equipment**

**Eye/face protection**

Splash proof goggles or safety glasses with side shields are recommended. Always wear eye protection when sanding cured epoxy to avoid dust in eyes.

|  |   |
|--|---|
| <b>Hand protection</b>                                 | Wear chemical resistant gloves such as: Poly Vinyl Alcohol (PVA), Viton, or Teflon gloves, apron, boots, head and face protection should be worn. The equipment must be cleaned thoroughly after each use.                                      |
| <b>Skin protection</b>                                 | Wear clean, body-covering clothing to avoid skin contact.   |
| <b>Respiratory protection</b>                          | Use a NIOSH-approved respiratory device or air-supplied respirator if exposure exceeds any occupational limits. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors. |
| <b>Special instructions for protection and hygiene</b> | Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands with warm, soapy water.  |

## 9. Physical and Chemical Properties

---

|   |                                  |
|---|----------------------------------|
| <b>Chemical family</b>                            | Translucent liquid               |
| <b>Appearance</b>                                 | Pourable liquid                  |
| <b>Physical State</b>                             |                                  |
| <b>Form</b>                                       | Pourable liquid                  |
| <b>Color</b>                                      | Amber                            |
| <b>Odor</b>                                       | Pungent odor                     |
| <b>Density (Specific Gravity)</b>                 | 0.877                            |
| <b>Viscosity</b>                                  | 600 – 750 CPS @ 25°C             |
| <b>pH</b>   | Data not available               |
| <b>Melting point/freezing point</b>               | Data not available               |
| <b>Initial boiling point and boiling range</b>    | 281-400°F                        |
| <b>Flash point</b>                                | 60°F (Pensky-Martens Closed Cup) |
| <b>Evaporation rate</b>                           | Slower than ether                |
| <b>Flammability (solid, gas)</b>                  | Data not available               |
| <b>Upper/lower flammability limit (by volume)</b> | Data not available               |
| <b>Upper flammability limit (by volume)</b>       | Data not available               |
| <b>Lower flammability limit (by volume)</b>       | Data not available               |
| <b>Material VOC</b>                               | 554 g/L                          |
| <b>Vapor density</b>                              | Heavier than air                 |
| <b>Relative density</b>                           | Data not available               |
| <b>Solubility in water</b>                        | Not determined                   |
| <b>Partition coefficient: n-octanol/water</b>     | Negligible, in water             |
| <b>Auto-ignition temperature</b>                  | Data not available               |
| <b>Decomposition temperature</b>                  | Data not available               |

## 10. Stability and Reactivity

---

|                   |                                 |
|-------------------|---------------------------------|
| <b>Reactivity</b> | Stable under normal conditions. |
|-------------------|---------------------------------|

|   |   |
|---|---|
| <b>Chemical Stability</b>                 | Stable.   |
| <b>Possibility of hazardous reactions</b> | Under normal conditions, hazardous polymerization will not occur.   |
| <b>Conditions to avoid</b>                | Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.  |
| <b>Incompatible materials</b>             | Strong oxidizing agents, Lewis and mineral acids.   |
| <b>Hazardous decomposition products</b>   | Oxides of carbon, aldehydes, acids.   |
| <b>Other hazards</b>                      | Epoxy resins and epoxy resin hardeners react with each other producing heat. They should not be mixed with each other under uncontrolled conditions or in large mass as the ensuing exotherm may result in heat and smoke, resulting in hazardous decomposition products. |

## 11. Toxicological Information

**Acute Health Hazard (components)** No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

| Component      | Result          | Species | Dose           | Exposure |
|----------------|-----------------|---------|----------------|----------|
| Polyaminoamide | LD50 Oral       | Rat     | >5,000 mg/kg   | -        |
| Xylene         | LD50 Oral       | Rat     | 4,300 mg/kg    | -        |
|                | LC50 Inhalation | Rat     | -              | 4h       |
| Ethylbenzene   | LD50 Oral       | Rat     | 3,500 mg/kg    | -        |
|                | LD50 Dermal     | Rabbit  | >5,000 mg/kg   | -        |
|                | LC50 Inhalation | Rat     | 55 mg/l        | 2h       |
| Acetone        | LD50 Oral       | Rat     | 5,800 mg/kg    | -        |
|                | LD50 Dermal     | Rabbit  | >115,800 mg/kg | -        |
|                | LC50 Inhalation | Rat     | 76 mg/kg       | 4h       |
| n-butanol      | LD50 Oral       | Rat     | 790 mg/kg      | -        |
|                | LD50 Dermal     | Rabbit  | 5,620 mg/kg    | -        |
|                | LC50 Inhalation | Rat     | >17.9 mg/l     | 4h       |

**Irritation/Corrosion** No information on the product itself.

**Sensitization** No information on the product itself.

**Mutagenicity** No information on the product itself.

**Carcinogenicity** No information on the product itself.

**Reproductive Toxicity** No information on the product itself.

**Teratogenicity** No information on the product itself.

**Specific target organ toxicity (single exposure)** No information on the product itself.

| Component      | Category   | Route of exposure | Target organs                                  |
|----------------|------------|-------------------|--|
| Polyaminoamide | Category 3 |                   | Respiratory tract irritation                   |
| Xylene         | Category 1 |                   | Central nervous system (CNS), liver, kidneys   |
|                | Category 3 |                   | Respiratory tract irritation, narcotic effects |

|              |            |  |  |
|--------------|------------|--|--|
| Ethylbenzene | Category 3 |  | Narcotic effects, Respiratory tract irritation |
| Acetone      | Category 3 |  | Central nervous system (CNS)                   |

**Specific target organ toxicity (repeated exposure)** No information on the product itself.

| Component      | Category   | Route of exposure | Target organs  |
|----------------|------------|-------------------|--|
| Polyaminoamide | Category 2 |                   | Skin   |
| Xylene         | Category 1 |                   | Respiratory tract irritation, Central nervous system (CNS)             |
| Ethylbenzene   | Category 2 |                   | Skin, eyes, liver, kidneys, respiratory tract irritation, blood system |
| Acetone        | Category 2 |                   | Kidney, liver, spleen, blood system                                    |

**Aspiration hazard** No information on the product itself.

**Potential acute health effects**

**Eye Contact**

Causes serious eye damage.

**Inhalation**

Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

**Skin Contact**

Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**

Can cause central nervous system (CNS) depression. May cause burns to mouth, throat, and stomach.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Eye Contact**

Adverse symptoms may include the following:  
Pain or irritation  
Watering  
Redness

**Inhalation**

Adverse symptoms may include the following:  
Nausea or vomiting  
Headache  
Drowsiness/fatigue  
Unconsciousness  
Reduced fetal weight  
Increase in fetal deaths  
Skeletal malformations

**Skin Contact**

Adverse symptoms may include the following:  
Pain or irritation  
Redness  
Reduced fetal weight  
Increase in fetal deaths  
Skeletal malformations

**Ingestion**

Adverse symptoms may include the following:  
Reduced fetal weight  
Increase in fetal deaths  
Skeletal malformations

**Delayed and immediate effects and also chronic effects from short and long term exposure** No information on product itself.

### Potential chronic health effects

|                              |   |
|------------------------------|---|
| <b>General</b>               | Causes damage to organs through prolonged or repeated exposure: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| <b>Carcinogenicity</b>       | No known significant effects or critical hazards.   |
| <b>Mutagenicity</b>          | No known significant effects or critical hazards.   |
| <b>Teratogenicity</b>        | May damage the unborn child.  |
| <b>Developmental effects</b> | No known significant effects or critical hazards.   |
| <b>Fertility effects</b>     | May damage fertility.   |

### Numerical measures of toxicity

#### Acute toxicity estimates (ATEmix)

| Route               | ATE value     |
|---------------------|---------------|
| Oral                | 2913.3 mg/kg  |
| Dermal              | 16789.8 mg/kg |
| Inhalation (vapors) | 36.59 mg/l    |

## 12. Ecological Information

### Ecotoxicity

No information on the product itself.

| Component    | Endpoint   | Result      | Species                               | Exposure |
|--------------|------------|-------------|---------------------------------------|----------|
| Xylene       | Acute LC50 | 13.4 mg/l   | Fish – Fathead minnow                 | 96 h     |
| Acetone      | Acute LC50 | 11,300 mg/l | Leuciscus idus melanotus              | 48 h     |
|              | Acute EC50 | 8,800 mg/l  | Daphnia magna (water flea)            | 48 h     |
|              | NOEC       | 430 mg/l    | Desmodesmus subspicatus (green algae) | 96 h     |
| Ethylbenzene | Acute LC50 | 9.09 mg/l   | Fish – fathead minnow                 | 4 d      |
|              | Acute LC50 | 4.2 mg/l    | Fish – Rainbow trout                  | 4 d      |
|              | Acute LC50 | 9.6 mg/l    | Fish – Guppy                          | 4 d      |
| n-butanol    | Acute LC50 | 1,376 mg/l  | Fathead minnow                        | 96 h     |
|              | Acute LC50 | 1,328 mg/l  | Water flea                            | 48 h     |

### Persistence and degradability

No information on the product itself.

### Bioaccumulative Potential

No information on the product itself.

| Component | LogPow | BCF | Potential |
|-----------|--------|-----|-----------|
| Xylene    | 3.12   | -   | -         |

### Mobility in Soil

**Soil/water partition coefficient (KOC)** No data is available on the product itself.

**Other adverse effects** No significant effects or critical hazards.



## 13. Disposal Considerations

|   |   |
|---|---|
| <b>Waste from residues/ unused products</b> | The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water. Contact supplier if guidance is required. |
| <b>Contaminated packaging</b>               | Dispose of container and unused contents in accordance with federal, state and local requirements.  |

## 14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

### International Transport Regulations

| Regulatory information | UN/NA number | Proper Shipping Name   | Classes/*PG | Additional Information |
|------------------------|--------------|------------------------|-------------|------------------------|
| DOT                    | UN1263       | Paint related material | Class 3 II  |                        |
| TDG                    | UN1263       | Paint related material | Class 3 II  |                        |
| IMO/IMDG               | UN1263       | Paint related material | Class 3 II  |                        |
| IATA                   | UN1263       | Paint related material | Class 3 II  |                        |

\*PG: Packing group

**Special precautions for user:** Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## 15. Regulatory Information

### UNITED STATES

#### U.S. Federal Regulations

**United States – TSCA 12(b) – Chemical export notification:** None Required.  
**United States – TSCA 5(a)2 – Final significant new use rules:** Not Listed.  
**United States – TSCA 5(a)2 – Proposed significant new use rules:** Not Listed.  
**United States – TSCA 5(e) – Substance consent order:** Not listed.

#### Clean Air Act – Ozone Depleting Substances (ODS)

This product does not contain nor is it manufactured with ozone depleting substances.

#### Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

| Product Name | Concentration % |
|--------------|-----------------|
| Ethylbenzene |                 |
| Xylene       |                 |

#### Pennsylvania – RTK

Ethyl benzene, Acetone

#### California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer. WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

| Ingredient Name | Cancer | Reproductive |
|-----------------|--------|--------------|
| Benzene, ethyl- | Yes.   | No.          |

|         |      |      |
|---------|------|------|
| Benzene | Yes. | Yes. |
|---------|------|------|

**EPA SARA 302 Extremely Hazardous Substances**

To the best of our knowledge, this product is not listed as an extremely hazardous substance.

**EPA SARA 302/304/311/312 Hazardous Chemicals**

This product should be reported as immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

**SARA 313 Form R – Reporting requirements**

| Product Name       | CAS number |
|--------------------|------------|
| Benzene, ethyl-    | 100-41-4   |
| Benzene, dimethyl- | 1330-20-7  |

**CERCLA Hazardous substances**

| Component | % | Section 304 CERCLA Hazardous Substance | CERCLA Reportable Quantity (Lbs) | Product Reportable Quantity (Lbs) |
|-----------|---|--|----------------------------------|-----------------------------------|
| Acetone   |   |  | 5000                             |                                   |

**United States inventory (TSCA 8b)**

All components are listed or exempted.

**CANADA**

**WHMIS (Canada)**

Class B-2: Flammable liquid.  
Class D-2B: Material causing other toxic effects (Toxic).

**Canadian NPRI  
CEPA Toxic substances**

None Required  
None Required

**INTERNATIONAL REGULATIONS**

**International Lists**

**Australia inventory (AICS):** All components are listed or exempted.  
**Canada inventory:** All components are listed or exempted.  
**Korea inventory:** All components are listed or exempted.  
**Japan inventory:** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**New Zealand inventory (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.  
**Taiwan inventory (CSNN):** All components are listed or exempted.

**16. Other Information, Including Date of Preparation or Last Revision**

**HMIS Rating**

|                 |   |
|-----------------|---|
| Health          | 2 |
| Flammability    | 3 |
| Physical Hazard | 0 |

|                              |                           |
|------------------------------|---------------------------|
| <b>Date of Preparation</b>   | January 22, 2020          |
| <b>Date of Last Revision</b> | September 26, 2019        |
| <b>Revision #</b>            | 5.0                       |
| <b>More Information</b>      | 1-253-333-8118            |
| <b>Prepared by</b>           | System Three Resins, Inc. |

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.